

PATENT

Express Mail number EL 756 224 286 US

Date of Deposit August 27, 2001

Case No. 3591-1154

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTORS:

Eric Ping Pang Chan - New York, New York
Rama Chorpash - New York, New York
Thomas William Granzow - Byron Center, Michigan
Andrew J. Kurrasch - Saugatuck, Michigan
Jeffrey Frederick Miller - New York, New York

TITLE:

TABLE

ATTORNEYS:

Andrew D. Stover
Reg. No. 38,629
Jeffery M. Duncan
Reg. No. 31,609
BRINKS HOFER GILSON & LIONE LTD.
P.O. Box 10395
Chicago, Illinois 60610
(312) 321-4200



00757

PATENT TRADEMARK OFFICE

TABLE

This application claims the benefit of U.S. Provisional Application S/N 60/229,210, filed August 31, 2000, the entire disclosure of which is hereby incorporated herein by reference.

5 BACKGROUND

The present invention relates generally to tables and work spaces, and in particular, to a table having an improved support structure, to a method for assembling the table and to an improved storage device.

10 Tables and desks of the type typically used in offices and the like are typically configured with complicated support structures that require a plurality of various fasteners and the like, and which usually are assembled by skilled installers and/or mechanics. Moreover, such support structures are often made of relatively heavy and expensive materials, which can increase the costs of manufacturing and shipping such structures. Indeed, because of
15 the difficulty in assembling such tables, various accessories, such as screens and the like, are not typically attached to the interface of the support structure and the work surface, but rather are otherwise attached with additional fasteners or mechanisms at other locations, or are separately supported on the floor. As such, additional parts typically are required to fully assemble the
20 work space, which in turn can increase the costs of manufacture and assembly thereof.

In addition, accessories, such as privacy screens, are generally planar in construction, and are typically disposed along, or attached to, one or more linear edges of a table. As such, typical privacy screens are two-dimensional,
25 and are not capable of providing three-dimensional coverage, for example over a corner of a desk.

In addition to these various shortcomings associated with various conventional tables and desks, office system storage devices are typically made of relatively heavy sheet metal or wood, which can be expensive to

manufacture and/or assemble. Moreover, such storage devices, with their relatively heavy weight, are not typically portable or mobile. As such, typically storage devices do not lend themselves to easy reconfiguration of a work space. In addition, such devices are generally only laterally accessible by way of doors or sliding drawers, which occupy an enlarged footprint when opened. Alternatively, certain storage devices have openings or are open on all sides thereof so as to expose the contents of the storage device, which may not be aesthetically pleasing.

SUMMARY

Briefly stated, in one aspect of the invention, one embodiment of a table comprises a support structure comprising a first wire support and a second wire support. Each of the first and second wire supports comprises opposite ends that are joined to define a first and second foot. A portion of each of the first and second wire supports form a first and second support platform respectively. The first wire support comprises a first segment extending upwardly from the first foot to the first support platform and a second segment extending from the first support platform to the second foot. The second wire support comprises a first segment extending upwardly from the second foot to the second support platform and a second segment extending from the second support platform to the first foot. A work surface is supported on the first and second support platforms.

In a preferred embodiment, the support structure further comprises a third wire support comprising opposite ends joined to the first and second feet. A portion of the third wire support forms a third support platform. The third wire support comprises a first segment extending from the first foot to the third support platform and a second segment extending from the second foot to the third support platform.

Also in a preferred embodiment, the support structure further comprises a first and second cap member disposed on an upper surface of said work surface. The first cap member is connected to the first support platform

and the second cap member is connected to the second support platform such that the work surface is clamped between the first and second cap members and the first and second support platforms respectively.

5 In another aspect of the invention, an accessory includes a mounting portion that is disposed between a surface of the work surface and one of the support platform and the cap member. The cap member is connected to the support platform with the mounting portion clamped between one of the support platform and the cap member and the work surface.

10 In yet another aspect of the invention, a privacy screen comprises a pole having a curved portion and a sheet material web. The sheet material web has a first edge portion connected to the pole and a second edge portion. The second edge portion is positioned such that the sheet material web has a non-planar contour. In a preferred embodiment, the sheet material web is made of a bi-directional stretchable material.

15 In a preferred embodiment, the screen comprises a mounting portion that is disposed between one of the support platform and the cap member and the work surface. Preferably, the pole extends out of a plane defined by the work surface.

20 In other aspects of the invention, methods for assembling a table and for providing privacy to a workspace are provided.

25 In yet another aspect of the invention, a storage device comprises a frame comprising a front and back frame member and a plurality of horizontal side frame members vertically spaced along opposite sides of the frame. The side frame members connect the front and back frame members. The front frame member is generally open. A sheet material web is disposed over at least the opposite sides of the frame to define a pair of side walls. The sheet material web is preferably connected to the frame adjacent the front frame member. In a preferred embodiment, the frame members are made of wire. Also in a preferred embodiment, the sheet material web is made of a flexible material, including for example, a fabric or plastic.

30

The present inventions provide significant advantages over other tables, desks and accessories, including for example, various screens and storage devices. For example, the support structure can be easily connected to the work surface with a minimal number of fasteners. In addition, the support structure, which is preferably made of wire, can be made inexpensively, and is relatively light weight. At the same time, the wire support structure provides a distinctive visual appearance to the table that is aesthetically pleasing.

In addition, the support structure can be easily, temporarily disconnected from the work surface, so as to allow an accessory to be mounted therebetween. In this way, the user avoids the need for additional fasteners and the like for attaching the accessory the table. At the same time, the accessory is rigidly connected to the robust support structure, rather than only to the work surface.

The privacy screen also provides distinct advantages over conventional screens. For example, the screen can be arranged to assume a three-dimensional contour. In this way, the screen can be disposed, for example, over the corner of a table to shield the user from both the back and side of the desk, as well as from above the desk. At the same time, the preferred bi-directional stretchable material allows the manufacturer to use a relatively simple two-dimensional pattern for the sheet material web that can be stretched into the three-dimensional configuration. The screen also is relatively lightweight and easy to assemble.

The storage device also provides significant advantages. In particular, the construction and materials of the frame and sheet material web make the storage device relatively lightweight, thereby allowing the user to easily move the storage device from one location to the next. Indeed, in a preferred embodiment, the storage device is provided with wheels to facilitate the mobility thereof. In addition, the sheet material web can be easily connected to the frame without the need for expensive fasteners and the like. Moreover, the storage device, which is preferably open both from the front and the top, can be easily accessed from the top and front without increasing the overall

foot print of the device. At the same time the storage device, with its frame and web, has a distinctive appearance with aesthetically pleasing features.

The present invention, together with further objects and advantages, will be best understood by reference to the following detailed description taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGURE 1 is a perspective view of a table with a screen, a hanger rail, a support accessory and a mounting member attached thereto.

FIGURE 2 is a front view of the table.

FIGURE 3 is a side view of the table.

FIGURE 4 is a bottom view of the table.

FIGURE 5 is an exploded perspective view of one embodiment of the table.

FIGURE 6 is a top view of the support structure.

FIGURE 7 is a side view of the support structure.

FIGURE 8 is a cross sectional view of the support structure taken along line 8-8 of FIG. 7.

FIGURE 9 is a cross-sectional view of a cap member.

FIGURE 10A is a two-dimensional screen fabric blank.

FIGURE 10B is a two-dimensional flat pattern of the screen.

FIGURE 11 is a side view of a mounting member.

FIGURE 12 is a top view of the mounting member.

FIGURE 13 is a partial bottom perspective view showing the attachment of the screen to the table.

FIGURE 14 is a perspective view of a support accessory.

FIGURE 15 is an end view of a cable trough.

FIGURE 16 is a cross-sectional view of a stem.

FIGURE 17 is an enlarged cross-sectional view of a foot of the support structure with a glide attached thereto taken along line 17-17 of FIG. 4.

FIGURE 18 is an enlarged cross-sectional view of an alternative embodiment of the support structure foot with a glide attached thereto.

FIGURE 19 is a perspective view of a storage device.

FIGURE 20 is a top view of the storage device frame.

5 FIGURE 21 is a side view of the storage device frame.

FIGURE 22 is a front view of the storage device frame.

FIGURE 23 is an enlarged front view of a side frame member with a file rail attached thereto.

10 FIGURE 24 is a view of a flat pattern layout of the storage device sheet material web.

FIGURE 25 is a perspective view of a storage tray.

FIGURE 26 is a top view of a second work surface.

FIGURE 27 is a side view of a pole.

15 DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

The terms “front”, “side”, “back”, “forwardly”, “rearwardly”, “upwardly” and “downwardly” as used herein are intended to indicate the various directions and portions of the table as normally understood when viewed from the perspective of a user facing the table. Likewise, the term “lateral” refers to the direction running the length of the table from one side to the other, while the term “longitudinal” refers to the direction running from the front to the back thereof.

Referring to the drawings, and as best shown in FIGS. 1-8 and 17, a preferred embodiment of a table includes a pair of support structures **20** positioned on opposite ends of the table. Each support structure **20** preferably comprises a first, second and third support members **22**, **24**, **26**, preferably each configured as a wire support. The first and second support members **22**, **24** each include opposite ends **28**, **30** that are joined to define in part a first and second foot **32**, **34**, with the first foot **32** preferably spaced longitudinally from the second foot **34**. The first support member **22** includes a first segment **36** that extends upwardly from the wire support member to a support platform

38. The support platform 38 is preferably formed in part by a portion of the first support member 22, which is formed into a U-shaped support segment 42. The support segment is preferably formed in a horizontal plane, and preferably has an inner diameter of about 0.78 inches. The term “support platform” means generally a member or portion that provides support, and should not be limited to a horizontal, planar or flat member or surface. In a preferred embodiment, the support platform further comprises a mounting plate 44, preferably circular, which is attached to an upper surface of the support segment 42, preferably by welding. The mounting plate 44 preferably has an opening therethrough positioned preferably in the center thereof. Preferably, the mounting plate 44 is welded to the support segment 42, although other means of attachment, such as adhesive, a snap-fit or mechanical fasteners could also be used.

The first support member 22 further comprises a second wire segment 40 extending downwardly and rearwardly from the support platform toward the second foot 34. Preferably, the first, second and support segments 36, 40, 42 are formed from a single piece of steel wire, preferably having about a 3/8 inch diameter.

The second support member 24 is substantially a mirror image of the first wire support, and includes a first and second wire segment 36, 40 joined at a support platform 38 comprising a U-shaped support segment 42. The support platform 38 further preferably comprises a mounting plate 44 attached to an upper surface of the support segment 42. Each of the support platforms 38 further comprises a threaded or male fastener 90 that extends upwardly through the opening in the plate member. In one embodiment, the fastener is welded to the plate member, although it can alternatively be threaded through the opening in the plate member 44, or be simply preferably inserted therethrough with the plate member acting as a washer.

Each support structure 20 further preferably comprises a third support member 26, also preferably formed as a wire support. The third support member 26 comprises opposite ends 46 that are joined to the ends 28, 30 of

the first and second wire support at each of the first and second feet **32, 34**. The third support member **26** includes a first segment **48** extending upwardly and laterally and longitudinally inwardly from the first foot **32** to a third support platform **52**, and a second segment **50** extending upwardly and laterally and longitudinally inwardly from the second foot **34** to the third support platform **52**. The third support platform **52** is preferably formed by a portion of the third support member **26**, which is formed into a U-shaped support segment **54**. The support segment **54** is preferably formed in a horizontal plane. A mounting plate member **44** is preferably attached to an upper surface of the support segment **54** to further define the third support platform **52**. Preferably, the three support platforms **38, 52** and in particular the upper surface of the mounting plates, lie in the same substantially horizontal plane.

Each of the ends **28, 30, 46** of the first, second and third support members **22, 24, 26** is substantially vertically oriented. In a preferred embodiment, the ends **28, 30, 46** of each support member are attached to form the first and second feet **32, 34**. Preferably, the ends are welded together.

Alternatively, each of the ends are inserted into an elongated stem **56**, best shown in FIGS. 2, 3, 16 and 17, having a cavity **58** opening to one end thereof. Preferably, the ends are first welded and then inserted into the cavity **58** of the stem, where they can then further be welded to the stem. The opposite end **62** of the stem includes a threaded opening **66**. The stem **56** has a longitudinally extending bore **64** connecting the threaded opening **66** and the cavity **58**. A glide **68** includes a housing **70** having a foot portion **72** and an upwardly extending stem **74**. The stem **74** preferably is hollow and opens to a top end **76** thereof. A threaded shaft **78** or bolt extends upwardly from the foot portion **72** into the hollow stem **74**. The shaft **78** engages the threaded opening **66** of the stem **56**, and can extend into the bore **64** as the glide **68** is threadably engaged with the stem **56**. The stem **56** is received in the stem **74**. In operation, the user rotates the glide **68** to adjust the relative height of one or more of feet **32, 34** to level the table **10**.

In an alternative embodiment, shown in FIGS. 5 and 18, the ends **28**, **30** of the first and second support members **22**, **24** are attached to an elongated stem **80** and, preferably to an outer surface **82** thereof by welding. The stem **80** has opposite open ends, both of which are preferably threaded. The ends **46** of the third support member each further include a collar **84** attached thereto, preferably by welding. The collar **84** is arranged a sufficient distance from the bottom of the end **46** such that it overlies a top **86** of the stem **80** as the third support member **26** is positioned adjacent the first and second supports members **22**, **24**. A fastener, preferably a threaded screw extends through the collar **84** and threadably engages the stem **80**. A glide **68**, preferably as described above, is threadably and adjustable engaged with the stem **80**, which includes a threaded opening and a bore and which is received in stem **74**.

As shown in FIGS. 1-5, a worksurface **12** is supported on a pair of support structures **20**, each configured with a pair of support platforms **38** and a support platforms **52**. It should be understood that more than two support structures, having two or three support members, can be used to support a work surface. In a preferred embodiment, the worksurface is made of prefaced particle board, and preferably a melamine faced particle board, although it should be understood that the worksurface could be made of any number of different materials, including metal, plastic, fiberglass, or other wood products. For example, in an alternative preferred embodiment, the worksurface is comprised of a 3 inch cell corrugated honeycomb core sandwiched between a pair of hardboard layers, and an upper surface preferably finished with a lacquer. The worksurface preferably has a convex side edges **18** and concave front and rear edges **14**, **16**. The worksurface preferably includes a bumper, preferably made of PVC, covering the edges thereof, and extending around the periphery of the work surface. The bumper is secured with fasteners, tangs, and adhesive or like fasteners. The worksurface **12** preferably has a plurality of openings **88** overlying the

openings formed in the mounting plate members 44 of the support platforms 38.

During installation, the user positions a bottom surface 126 of the work surface 12 on top of the support platforms 38, 52 with the fasteners 90 or shaft extending upwardly into the opening 88 formed through the worksurface 12.

A cap member 92 is then installed to connect the work surface to the support platforms 38. In a preferred embodiment, the cap member 92 comprises a circular cap portion 94 and a stem portion 96 extending outwardly therefrom. The cap portion 94 preferably includes curvilinear top portion 98. In an alternative embodiment, the cap member includes a flat bottom portion 100, which is preferably formed as a plate member 100 attached to the cap member. Preferably, the cap member is made of an ABS material or hard plastic, although it could be made out of metal or any other suitable material. The top portion 98 defines a recess 102 in the middle of the cap member. The stem 96 further includes an insert 104 having a threaded opening 106 formed longitudinally therein. The insert 104, which is preferably brass, is press fit into a longitudinally extending cavity 108 formed in the stem. Alternatively, the insert can be secured in the stem with adhesives and the like. The stem 96 of the cap member 92 is inserted into the opening 88 formed in the work surface 12, such that the threaded opening in the insert is threadably engaged with the fastener 90 extending upwardly from the support platform 38. In one embodiment, the cap member 92 includes a lip portion 103 formed around a periphery thereof. The lip portion 103 engages and preferably flexes against a top surface 112 of the work surface. Alternatively, a bottom surface of the plate member of the cap member engages the top surface of the work surface. The cap member 92, or the fastener 90, is rotated by the user, and is threadably engaged with fastener 90 or member 92 respectively, to clamp the work surface 112 to the support platforms 38 in a simple easy operation. When installed, the cap portion 94 of the cap member preferably has at least a portion raised above the top surface 112 of the work surface 12, as shown for example in FIGS. 2 and 3.

In an alternative embodiment, the cap member comprises a downwardly extending threaded shaft that is threadably engaged with a threaded opening formed in the mounting plate. The cap member is rotated to clamp the worksurface between the cap and the support platforms.

5 When the third support member is employed, a fastener 114 is inserted through the opening in the plate member 44 and is directly threadably engaged with the work surface member 12. Alternatively, an insert is embedded in a bottom surface of the worksurface. The insert includes a threaded opening that threadably receives the fastener 114. Of course, it should be understood
10 that the work surface could further be secured to the third support platform with a cap member, as described above, but that in a preferred embodiment, it is preferred that the work surface be maintained flat and free of obstacles in the region overlying the third support platform 52. If a cap member is used to secure the worksurface to the third support platform, the cap position is
15 preferably recessed completely in the worksurface such that it does not have any portion raised thereabove.

In a preferred embodiment, a second work surface 116 or cover shown in FIG. 26, which is preferably thinner than the first work surface, is disposed on the upper surface 112 of the first, lower work surface 12. The second work
20 surface 116 or cover is preferably made of MATTE PETG sheet, and is preferably about 0.02 inches thick. The second work surface 116 has four openings 118 dimensioned to receive the cap member 92. In this way, the second work surface 116 is placed on top of the first work surface 12, with the openings 118 indexed on the cap portion 94 of the cap members 92. The user
25 can easily replace or remove the second work surface as desired, for example, to alter the color, surface texture or material of the second work surface as desired. In addition, the second work surface 116 can be easily removed for cleaning or disposal as needed, with a replacement work surface 116 easily
30 disposed on the work surface 12. Although the second work surface is preferably disposed on the first work surface, without other attachment devices, it should be understood that the two work surfaces could be joined

with adhesives, Velcro and/or other types of fasteners, including various mechanical fasteners. The second work surface preferably has substantially the same shape as the lower work surface **12**, including opposite convex side edges **18** and concave front and rear edges **14**, **16**, although it preferably is dimensioned to leave a slight reveal of the upper surface of the first work surface around the peripheral edge thereof.

Referring to FIGS. 1-5, an accessory is shown as being supported on the table. The accessory, shown as a hanger rail **120**, preferably includes a curvilinear rail, which is preferably formed in a horizontal plane, and which preferably has a contour that maps the contour of, and is spaced substantially equidistance from, the side edge **18** of the work surface **12**. The ends **122** of the rail are curved inwardly and are connected to a mounting portion **123**, preferably formed as a plate member having a slot **124** formed therein. Various storage devices, such as bags **127**, hangers, trays and the like can be suspended from the rail. During installation, the cap member **92** is loosened from its connection with the support platforms **38**, **52**. The mounting portion **123** is then preferably slid between the support platform **38** and the bottom surface **126** of the work surface **12**, with the fastener **88** received in the slot **124** formed in the mounting plate **123**. The mounting plate further includes a hole **125**, which is used to suspend the mounting plate as it is painted or otherwise finished. Of course it should be understood that fasteners also could be inserted through the hole **125** to attach the mounting plate to the table. In an alternative embodiment, the mounting plate is disposed between the cap portion and the upper surface of the work surface and clamped therebetween. In either embodiment, the cap member **92**, or fastener **90**, is then again tightened to clamp the work surface **12** and the accessory, or its mounting portion **123**, between the cap member **92** and the support platform **38**. In this way, an accessory can be easily attached to the table without the need for complicated mechanisms and fasteners. Moreover, the accessory is directly attached to the support structure, so as to provide a more robust support therefore. Once the accessory is attached to one or more support

platforms **38, 52**, the glide **68** attached to the foot or feet **32, 34** therebeneath can be rotated to lower the work surface **12** as needed, since it has now been raised a slight amount due to the additional thickness of the mounting plate **123**.

5 Other accessories include a mounting member **128**, shown in FIGS. 2-4, 11 and 12, preferably formed as a hook member from a tube, which has an L-shaped configuration with a horizontal leg **131** and a vertical leg **130**. The mounting member **128** is attached to a mounting plate **123** having a slot **124** and an opening **125**. The upstanding leg portion **130** is
10 preferably spaced from the edge **14, 16, 18** of the work surface such that various items, for example personal articles such as a hat or coat, can be engaged thereon. The legs **130, 131** are preferably formed from a tube, or solid wire. The mounting member plate can be inserted between the support platform **138** and the bottom surface of the work surface, or between the top surface thereof and the cap member. Alternatively, the plate member **123** can
15 be simply mounted to a top or bottom surface of the work surface with adhesive, mechanical fasteners and the like, or some combination thereof.

Referring to FIGS. 1, 10A, 10B, 13 and 27, yet another accessory is formed as a screen **134**. The screen **134** preferably includes a flexible pole
20 **136**, which is curved and extends out of a plane defined by the work surface **12**. The pole is preferably made of fiberglass. As best shown in FIG. 27, the pole **136** includes an elongated tube **125** and a tubular insert **127**, which is received in each end of the tube **125**. Opposite ends **138** of the pole **136** are disposed in or connected to the mounting member **128**. Preferably, the
25 ends **138** of the pole inserts **127** are inserted into the hollow tube of the mounting member, which forms the upstanding leg **130**. Preferably, the outer diameter of the tube **125** is substantially the same as the outer diameter of leg **130**, so as to provide a continuous appearance as the insert **127** connects the tubes. The mounting plate **123** is preferably mounted between one of the support platform or the cap member and the work surface, as set forth above.
30 Preferably, as shown in FIG. 11, the mounting plate **123** is disposed on one of

the support platforms **38** positioned adjacent the front edge **14** of the table **10**. The opposite end of the pole is preferably mounted to a mounting member **128** attached beneath the work surface at an approximate mid portion of the rear edge thereof.

5 The screen **134** preferably includes a sheet material web **140** made of a bi-directional stretchable material, such as a woven or knitted fabric preferably made of 85% nylon and 15% lycra. It should be understood that the bi-directional material can be stretched in any number of directions, e.g., diagonally and is not limited to stretching in only two directions. In this way,
10 the sheet material web **140** can be cut from a simple two-dimensional pattern, as shown in FIG. 8A and 8B, and thereafter attached to the pole **136**, wherein it can be stretched to assume various three-dimensional (3-D) configurations. In a preferred embodiment, shown for example in FIG. 1, one end **138** of the pole **136** is connected to the work surface, or table, along a side edge or corner
15 thereof, while the opposite end of the pole is connected to the work surface or table, along a rear edge thereof. Of course, it should be understood, that the ends of the pole could be secured along opposite sides of the table, along the front and back edges of the table, or along the same edge thereof. Likewise, the screen could be mounted or secured to a table having a non-rectangular
20 work surface, such as a circular, oval or elliptical work surface, wherein opposite ends of the pole are merely spaced apart along the edge of the work surface.

In a preferred embodiment, as best shown in FIGS. 1, 10 and 13, the sheet material web **140** has a first edge portion **142**, preferably formed as a
25 loop **144**, connected to the pole **136**, preferably by inserting the pole **136** through the loop **144**. The first edge **142** is preferably curved. The sheet material web **140** further includes a second edge portion **146**, otherwise referred to as a free edge. The free edge **146** of the sheet material web is disposed beneath the work surface **12** such that the sheet material web
30 engages one or more edges **14**, **16**, **18** of the work surface **12**. The free edge preferably comprised a middle edge **148**, having a curved portion, and two

side edges **150**. A pair of ties **152**, which are preferably elastic straps, extend from the free edge, preferably at a junction between the side and middle edges. A pair of loops **154** or alternatively a pair of secondary ties, extend from the edge **150** adjacent a curved junction **156** formed between the first and second edges **142**, **146**. The ties **152** or straps are preferably pulled so as to stretch the sheet material web tight between the edges **16**, **18** of the work surface and the pole **136**. In one embodiment, the ties **152** are secured to the support structure, and in particular the support platform **52** or other mounting points, beneath the work surface **12** so as to stretch the sheet material web between the edges **16**, **18** of the work surface and the pole **136**. The ties **152** preferably terminate in loops **155** which can be connected and engaged by a hook, e.g., an S-shaped hook. In such an embodiment the ties are stretched to pull the sheet material web tight. The loops **154** can further be secured to or threaded over the mounting member **128** so as to help stretch the sheet material web **140** and maintain a smooth contour thereof.

Due to the curved nature and orientation of the pole, and the non-linear contour of the side and rear edges **16**, **18** of the work surface **12**, the sheet material web **140** assumes a non-planar, or 3-D contour. In a preferred embodiment, wherein the sheet material web **140** is stretched over a portion of a side and rear edge **18**, **16** of the work surface, the sheet material web **140** assumes a unique half-dome shape having a convex outer surface. The screen is an ideal accessory for providing privacy from the back and side of the table, as well as from overhead, for example when shading from an overhead light is desired. In addition, the screen **134** is relatively light weight and easy to install in a variety of different positions.

Referring to FIGS. 1-4 and 15, a utility raceway **158**, or trough, is shown as being attached to the work surface along the rear edge thereof. The raceway is preferably made of a flexible PVC material, which is preferably extruded. The raceway **158** has a generally U-shaped trough, with a bottom cavity **160** preferably having a greater diameter or width than the width of the mouth **162** of the trough. A horizontally extending mounting flange **164**

extends outwardly from end of the trough, and is secured to the bottom **126** of the work surface with a plurality of fasteners. The opposite end of the trough terminates in a bead **166**, which is spaced from and hangs loose adjacent the rear edge of the table. The outer surface **168** of the trough includes a plurality of longitudinally extending rib portions **170**, which provide additional strength and rigidity to the raceway. In operation, various utilities, including phone lines, electrical cords, computer wires and the like, can be run over the rear edge **16** of the work surface **12** and be disposed in the raceway **158** for storage and the like. Alternatively, various items such as excess cords, lines, or even papers and documents, can be stored in the raceway. As shown in FIG. 1, various openings **171** can be formed in the bottom of the trough to allow passage of the utilities to outlets and the like on the floor positioned beneath the table.

Referring to FIGS. 1 and 14, a support accessory **172** is shown as comprising a base wall **174** and an upwardly extending back wall **176**. A stand **178** is connected to the support accessory, and preferably includes a pair of legs **180** that are supported on top of the uppermost work surface **116**. A pair of support feet **182** extend downwardly from a front portion of the base wall and form a pair of rails **184**, which extend rearwardly beneath the support accessory and engage the work surface **116**. The support feet **182** further include a pair of supports that extend beneath the worksurface. Various documents and other articles can be supported on the support accessory, and in particular are rested on the base wall **174** and leaned against the back wall **176**.

Referring to FIGS. 1 and 19-25, a storage device **200** is shown as including a frame **202** and a sheet material web **204**. The frame **202** includes a front and back frame member **206**, **208**, which are preferably formed from a wire and preferably have a generally rectangular shape, with a pair of vertical members **212**, **216** and a pair of horizontal members **214**, **215** joined thereto. The vertical members **212** on the front frame member **206** are preferably longer than the vertical members **216** on the back frame member **208**. The

frame further includes a plurality of vertically spaced side frame members **218**, also preferably made of wire, that extend between and connect the front and back frame members **206**, **208**, and in particular the vertical members **212**, **216** thereof. The side frame members **218** preferably include curved end portions **220**, and a linear middle portion **222** which extends inwardly from the side of the storage unit. Referring to FIGS. 22 and 23, a rail **232** can be attached to one or more of the side frames **218**, and preferably the uppermost side frames. The rails **232** on opposite side frames are spaced to support letter or legal sized, file holders **234**, which have hook members **236** that are slidably supported on the rails **232**. The rails **232** are preferably welded to the side frames **218**. As shown in FIGS. 19, 20 and 22, the frame is generally open to the front, rear, bottom and top. The frame is further open along the sides thereof between the plurality of side frame members **218**, as shown in FIG. 21.

The vertical members of the front and rear frame members each include an upper and lower portion **224**, **226** that are angled slightly forward and rearward respectively. The upper horizontal frame member **214** of the front frame member **206** forms a convenient handle for the storage unit that can be grasped by the user to lift the lower member **214** off of the floor. The lower horizontal frame members **214**, **215** on each of the front and rear frames **206**, **208** provide a pair of support feet for the storage device. In a preferred embodiment, a pair of wheels **228** are secured to an axle **230**, which is attached preferably to the rear frame **208** on the lower frame member **215** thereof. A pad can be disposed around the lower horizontal frame member **214** of the front frame **206** so as to cushion the frame and so as to prevent damage to the floor or other support surface. In use, the user can grasp the upper horizontal frame member **214** of the front frame member **206** as a handle and wheel the storage device from one location to another.

The sheet material web **204**, best shown in FIGS. 19 and 24, is preferably made of a flexible material, such as a woven fabric. In a preferred embodiment, the sheet material web is made of a flexible, semi-resilient

plastic or a thermoplastic sheet, and is preferably made of PETG. The sheet material web can be made transparent, opaque or solid. In one embodiment, the sheet material web is wrapped around four surfaces of the frame, and preferably, the top, bottom and opposite sides thereof.

5 In an alternative embodiment, best shown in FIG. 19, the sheet material web is wrapped around three surfaces defined by the frame, including the rear and opposite sides of the frame. In this embodiment, the top, bottom and front of the storage device **200** remain generally open. As shown in FIG. 24, the sheet material web **204** includes four columns of a plurality of
10 vertically spaced openings **238**. Two pairs of columns are each spaced a distance approximate the distance between the front and back frame members **212**, **216**. The openings **238** in each column are vertically spaced so as to be aligned with the side frame members **218**. A plurality of slits **240** are made in the web **204** and connect the horizontally displaced openings in each pair of columns. The sheet material web preferably is disposed inside the
15 frame on the side frame members **218** by piercing the web **204** at the slits **240** with the side frame members **218**. After the web **204** as passed over the side frame members, and in particular portions **222**, at the slits **240**, the slits **240** close and the side frame members, and in particular the curved portions thereof, extend through the openings **238** formed in the web. By way of the
20 piercing of the sheet material web by the side frame members, the sheet material web is secured to the frame. The outer surface of the edges **241** of the web rest or abut against the inner surface of the vertical front frame members **212**.

25 As best shown in FIGS. 19 and 25 the storage device **200** further includes a tray **242** having side walls **244**, a bottom **247** and a front and back wall **246**. The front and back wall preferably include a plurality of openings **256** formed therein. The side walls include an outwardly extending flange **250** that engages and slides on opposite side frame members **218**. The
30 top edge of the end of the front and back walls **246** and the flange **250** form an opening through which the side frame member **218** is received.

5